

## MERCEDES SPRINTER PANEL VAN



2017

## Short panel van with Standard Roof or High Roof

Standard Roof High Roof

### Panel Short, Standard Roof

Vehicle length/GVW	Short 3.0t	Short 3.5t
Wheelbase (mm)	3250	3250
Kerb weight (kg) for perm. GVW*	2088 - 2202*	2097 - 2191*
Payload [kg]	798 - 912	1309 - 1403
Perm. Gross Combination Weight [kg]**	3000 / 5000**	3500 / 5500 / 6300 / 7000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	300   2000 / 750	300   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	4.4   7.5   2600	4.4   7.5   2600
Turning circle Ø [m]   track circle Ø [m]	12.3   11.3	12.3   11.3

\*Stated figures in accordance with Directive 97/27/EC in the applicable version at the time of going to press. (With driver (75kg), all service fluids and tank 90% full). Figure also includes all UK standard specification features

\*\*Upated permissible gross combination weight in conjunction with reinforced trailer coupling (optional extra), depending on the powertrain variant – except for the 316NGT

## Short panel van with Standard Roof or High Roof

Standard Roof [High Roof](#)

### Panel Short, High Roof

Vehicle length/GVW	Short 3.0t	Short 3.5t
Wheelbase (mm)	3250	3250
Kerb weight (kg) for perm. GVW*	2123 - 2237*	2132 - 2226*
Payload [kg]	763 - 877	1274 - 1368
Perm. Gross Combination Weight [kg]**	3000 / 5000**	3500 / 5500 / 6300 / 7000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	150   2000 / 750	150   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	4.4   8.5   2600	4.4   8.5   2600
Turning circle Ø [m]   track circle Ø [m]	12.3   11.3	12.3   11.3

\*Stated figures in accordance with Directive 97/27/EC in the applicable version at the time of going to press. (With driver (75kg), all service fluids and tank 90% full). Figure also includes all UK standard specification features

\*\*Upated permissible gross combination weight in conjunction with reinforced trailer coupling (optional extra), depending on the powertrain variant – except for the 316NGT

2017

## Medium panel van with Standard Roof, High Roof or Super-high Roof

Standard Roof High Roof Super-high Roof

### Panel Medium, Standard Roof

Vehicle length/GVW	Medium 3.0t	Medium 3.5t	Medium 4.6t	Medium 5.0t
Wheelbase (mm)	3665	3665	3665	3665
Kerb weight (kg) for perm. GVW*	2172 - 2286*	2185 - 2429*	2233 - 2314*	2468 - 2510*
Payload [kg]	714 - 828	1315 - 1071	2286 - 2367	2490 - 2532
Perm. Gross Combination Weight [kg]**	3000 / 5000**	3500 / 5500 / 6300 / 7000**	6600 / 7000**	6000 / 7000 / 8000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	300   2000 / 750	300   2000 / 750	300   2000 / 750	300   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	5.2 - 5.5   9.0   3265	5.2 - 5.5   9.0   3265	5.2 - 5.5   9.0   3265	5.2 - 5.5   9.0   3265
Turning circle Ø [m]   track circle Ø [m]	13.6   12.6	13.6   12.6	13.6   12.6	13.6   12.6

2017

## Medium panel van with Standard Roof, High Roof or Super-high Roof

Standard Roof **High Roof** Super-high Roof

### Panel Medium, High Roof

Vehicle length/GVW	Medium 3.0t	Medium 3.5t	Medium 4.6t	Medium 5.0t
Wheelbase (mm)	3665	3665	3665	3665
Kerb weight (kg) for perm. GVW*	2202 - 2316*	2215 - 2459*	2263 - 2344*	2498 - 2540*
Payload [kg]	684 - 798	1285 - 1315	2256 - 2337	2460 - 2502
Perm. Gross Combination Weight [kg]**	3000 / 5000**	3500 / 5500 / 6300 / 7000**	6600 / 7000**	6000 / 7000 / 8000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	150   2000 / 750	150   2000 / 750	150   2000 / 750	150   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	5.2 - 5.5   10.5   3265	5.2 - 5.5   10.5   3265	5.2 - 5.5   10.5   3265	5.2 - 5.5   10.5   3265
Turning circle Ø [m]   track circle Ø [m]	13.6   12.6	13.6   12.6	13.6   12.6	13.6   12.6

2017

## Medium panel van with Standard Roof, High Roof or Super-high Roof

Standard Roof High Roof Super-high Roof

### Panel Medium, Super-high Roof

Vehicle length/GVW	Medium 3.5t	Medium 4.6t	Medium 5.0t
Wheelbase (mm)	3665	3665	3665
Kerb weight (kg) for perm. GVW*	2245 - 2489*	2293 - 2374*	2528 - 2570*
Payload [kg]	1255 - 1011	2226 - 2307	2490 - 2472
Perm. Gross Combination Weight [kg]**	5500 / 6300 / 7000**	6600 / 7000**	6000 / 7000 / 8000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	-   2000 / 750	-   2000 / 750	-   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	5.2 - 5.5   11.5   3265	5.2 - 5.5   11.5   3265	5.2 - 5.5   11.5   3265
Turning circle Ø [m]   track circle Ø [m]	13.6   12.6	13.6   12.6	13.6   12.6

2017

## Long panel van with High Roof or Super High Roof

[High Roof](#) [Super-high Roof](#)

### Panel Long, High roof

Vehicle length/GVW	Long 3.5t	Long 4.6t	Long 5.0t
Wheelbase (mm)	4325	4325	4325
Kerb weight (kg) for perm. GVW*	2371 - 2465*	2443 - 2524*	2679 - 2722*
Payload [kg]	1129 - 1035	2076 - 2157	2278 - 2303
Perm. Gross Combination Weight [kg]**	3500 / 5500 / 6300 / 7000**	6600 / 7000**	6000 / 7000 / 8000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	150   2000 / 750	150   2000 / 750	150   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	7.1 - 7.4   14   4300	7.1 - 7.4   14   4300	7.1 - 7.4   14   4300
Turning circle Ø [m]   track circle Ø [m]	15.6   14.6	15.6   14.6	15.6   14.6

## Long panel van with High Roof or Super High Roof

High Roof [Super-high Roof](#)

### Panel Long, Super-high Roof

Vehicle length/GVW	Long 3.5t	Long 4.6t	Long 5.0t
Wheelbase (mm)	4325	4325	4325
Kerb weight (kg) for perm. GVW*	2401 - 2495*	2473 - 2554*	2709 - 2752*
Payload [kg]	1099-1005	2046 - 2127	2248 - 2373
Perm. Gross Combination Weight [kg]**	3500 / 5500 / 6300 / 7000**	6600 / 7000**	6000 / 7000 / 8000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	-   2000 / 750	-   2000 / 750	-   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	7.1 - 7.4   15.5   4300	7.1 - 7.4   15.5   4300	7.1 - 7.4   15.5   4300
Turning circle Ø [m]   track circle Ø [m]	15.6   14.6	15.6   14.6	15.6   14.6



2017

## Extra-long panel van with High Roof or Super-high Roof

[High Roof](#) [Super-high Roof](#)

### Panel Extra-long, High Roof

Vehicle length/GVW	Extra-Long 3.5t	Extra-Long 4.6t	Extra-Long 5.0t
Wheelbase (mm)	4325	4325	4325
Kerb weight (kg) for perm. GVW*	2425 - 2519*	2512 - 2593*	2747 - 2789*
Payload [kg]	981 - 1075	2007 - 2088	2211 - 2253
Perm. Gross Combination Weight [kg]**	3500 / 5500 / 6300 / 7000**	6600 / 7000**	6000 / 7000 / 8000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	150   2000 / 750	150   2000 / 750	150   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	7.8 - 8   15.5   4700	7.8 - 8   15.5   4700	7.8 - 8   15.5   4700
Turning circle Ø [m]   track circle Ø [m]	15.6   14.6	15.6   14.6	15.6   14.6

2017

## Extra-long panel van with High Roof or Super-high Roof

High Roof [Super-high Roof](#)

### Panel Extra-long, Super-high Roof

Vehicle length/GVW	Extra-Long 3.5t	Extra-Long 4.6t	Extra-Long 5.0t
Wheelbase (mm)	4325	4325	4325
Kerb weight (kg) for perm. GVW*	2455 - 2549*	2542 - 2623*	2777 - 2819*
Payload [kg]	951 - 1055	1977 - 2058	2181 - 2223
Perm. Gross Combination Weight [kg]**	3500 / 5500 / 6300 / 7000**	6600 / 7000**	6000 / 7000 / 8000**
Maximum roof load [kg]   towing capacity braked/unbraked [kg]	-   2000 / 750	-   2000 / 750	-   2000 / 750
Loading area [m <sup>2</sup> ]   loading volume [m <sup>3</sup> ]   max. loading length	7.8 - 8   17   4700	7.8 - 8   17   4700	7.8 - 8   17   4700
Turning circle Ø [m]   track circle Ø [m]	15.6   14.6	15.6   14.6	15.6   14.6